



NEXT-GENERATION DC CHARGING SOLUTION

Fast. Reliable. Built for the Future.

DC FAST CHARGER

140 kW, 60 Hz, Emergency Mobile Energy Delivery System - DC Fast Charging and AC Available

Standard Features

- 60-320 kW DC output range
- Dual CCS1 connectors (up to 300A each)
- Three-phase AC input (260-530V, 45-65 Hz)
- IP54 weather-resistant enclosure and optimized forced-air cooling
- Built-in over-current, under-voltage, surge, and leakage protection
- Modular design for scalable capacity
- 21" touchscreen interface with QR code, RFID, or password authentication
- OCPP 1.6J / OCPP 2.0.1 network compatibility
- Operating temperature range: -25°C to 55°C (5-95% humidity)





OMEGA Typical Use Case

- **Roadway and travel hub charging** keep EVs moving along popular driving routes and at key travel stops. **Fleet depot fast charging** keep electric buses, trucks, and service vehicles mission-ready with high-power turnaround.
- **Retail and hospitality charging** attract customers with convenient, fast charging at shopping centers, hotels, and restaurants.
- Workplace EV support provide employees and visitors with reliable high-speed charging during the workday
- Urban and municipal charging expand citywide EV infrastructure to meet growing public demand.

1





NEXT-GENERATION DC CHARGING SOLUTION

Fast. Reliable. Built for the Future.

| Specification | OMEGA |
|-----------------------|-------------------------------------|
| Output Type | DC Fast Charging (200–1000V) |
| Power Output Options | 60 kW – 320 kW |
| Charging Connectors | 2 (CCS1, NACS compatible) |
| Max Output Current | 300 Amps per connector |
| Input Voltage Range | 260–530V AC, 3-Phase (Nominal 400V) |
| Input Frequency | 45–65 Hz |
| Power Factor | ≥ 0.99 (above 50% load) |
| Cooling Method | Air-Cooled |
| Charging Cable Length | 18' |
| Cable Management | Spring Gear Retractor |
| Display & Interface | 21" Touchscreen + QR/RFID/Password |





NEXT-GENERATION DC CHARGING SOLUTION

Fast. Reliable. Built for the Future.

| Specification | OMEGA |
|-------------------------|---|
| Communication Protocols | Ethernet, 3G/4G, WiFi; OCPP 1.6J/2.0.1 |
| Safety Features | Overcurrent, Undervoltage, Residual Current, Short Circuit, Overtemp, Surge & Leakage Protection |
| Environmental Ratings | IP54, -13°F to131°F, 5–95% RH |
| Dimensions | 84" (H) x 42" (W) x 34" (D) |
| Standards Compliance | ETL, UL (Cables & Connectors only) |





Get in Touch

2360 Clark St, STE C, Apopka, FL 32703 http://www.chargerigs.com (321) 396-0367 Charge Rigs LLC. All Rights Reserved.



Proudly Built in Apopka, FL

