



Gasoline or Propane-Powered Generator with Integrated Level 2 EV Charger

Dual-Fuel Mobile Power & EV Charging System

Helix 252K-240: 240 kW Battery Energy Storage System with DC Fast Charger | 150-1000Vdc Output

Standard Features

- Dual-fuel operation runs on gasoline or propane
- Integrated Level 2 EV charger (up to 11.5 kW)
- Adjustable amperage with app-based finetuning
- All-metal, weather-resistant construction
- GFCI-protected outlets and built-in safety protections
- Push-button electric start with recoil backup
- Wheel and handle kit with 10" metal hub wheels
- IP66-rated charger enclosure
- Wi-Fi connectivity for charger monitoring
- Copper winding generator with automatic voltage regulation



APEX Typical Use Case

- Remote EV charging provide on-demand charging where permanent infrastructure isn't available
- Backup charging during power outages keep EVs operational when the grid goes down
- Fleet vehicle support deliver supplemental charging for service, delivery, or municipal fleets
- **Event and temporary site power** supply electricity and EV charging for outdoor events, construction sites, or pop-up operations
- Off-grid living and recreation power EVs, tools, and appliances at cabins, campsites, or remote
 properties

1





Gasoline or Propane-Powered Generator with Integrated Level 2 EV Charger

Specifications	Apex
Overview	Dual-fuel generator + integrated Level 2 EV charger. Runs on gasoline or propane for on-demand or backup power.
Gasoline Mode	Peak Wattage: 13,000 W Running Wattage: 10,500 W Running Amperage (120V): 87.5 A Running Amperage (240V): 43.75 A Runtime (25% Load): ~17 hrs Runtime (50% Load): ~8 hrs
Propane Mode	Peak Wattage: 12,350 W Running Wattage: 9,975 W Running Amperage (120V): 83.13 A Running Amperage (240V): 41.56 A Runtime (25% Load): ~13 hrs Runtime (50% Load): ~6 hrs
EV Charging Capability	Max Output: 11.5 kW (240V AC 48A) if hardwired Default Output: 9.6 kW (240V AC 40A) with NEMA 14-50 plug Adjustable Amperage (Internal Switch): 16A, 32A, 40A (default), 48A Fine-Tune Current: 6A increments up to selected max via app





Gasoline or Propane-Powered Generator with Integrated Level 2 EV Charger

Specifications	Арех
Engine & Fuel System	Type: 4-Stroke OHV, forced air cooling
	Size: 500 cc
	Speed: 3600 RPM
	Starting Method: Push-button electric + recoil
	Idle Control: No-load low idle
	Fuel Types: Gasoline or propane
	Fuel Delivery: Carburetor
	Fuel Tank Capacity (Gasoline): 8.3 gallons
	Fuel Gauge: Yes
	Oil Type: 10W-30 (blended, conventional, or synthetic)
	Oil Capacity: 40.5 fl oz (1.2 L)
	Automatic Low Oil Shutdown: Yes
	CO Sensor Shutdown: No
	EPA Certified: Yes
Panel & Outlets	GFCI Protected Outlets: Yes
	Battery Switch: Yes
	Voltmeter: Digital
	Hour Meter: Yes
	Outlets: (2) 120V 5-20R, (1) 120V 30A L5-30R, (1) 120/240V 30A L14-30R, (1)
	120/240V 50A 14-50R, (1) 12V automotive
Operating Conditions	Charger Operating Temp: -22°F to 122°F (-30°C to 50°C)
	Noise Level (Generator): ~74 dB





Gasoline or Propane-Powered Generator with Integrated Level 2 EV Charger

Specifications	Apex
Electrical & Protections	Voltage Range: 120/240V, 60 Hz Winding Material: 100% copper
	Automatic Voltage Regulator: Yes
	Protections (Charger): Overcurrent, current leakage, overvoltage,
	undervoltage, overheat, surge, relay fault, control pilot fault, voltmeter
	fault
	Network Connection: Wi-Fi 2.4 GHz
	Enclosure Rating (Charger): IP66
Dimensions & Weight	Size: 29" L × 30" W × 26" H
	Dry Weight (Generator Only): ~234 lbs
	Total Weight (With Accessories): ~248 lbs
	Construction: All-metal
	Wheel & Handle Kit: Included (10" metal hub wheels)
Warranty	Generator: 3 years (limited)
	Charger: Refer to installer/manufacturer for details





Get in Touch

2360 Clark St, STE C, Apopka, FL 32703 http://www.chargerigs.com (321) 396-0367 Charge Rigs LLC. All Rights Reserved.



Proudly Built in Apopka, FL

